



Transom Sizes

1. The window drawings in this catalog are not necessarily all scaled the same. Drawings are intended for visual reference only and are not suitable for architectural purposes.
2. The Call Size is a unique identification number for the product type and size. Use this number to specify unit and size wanted.
3. Unit / Frame Width = Call Width + 4" x Qty wide. Specified in inches.
4. Unit / Frame Height = Call Height + 4". Specified in inches.
5. Rough Opening Width = Unit/Frame Width + 1/2". Specified in feet and inches.
6. Rough Opening Height = Unit/Frame Height + 1/2". Specified in feet and inches.
7. A dimension page at the back of this section gives precise specifications for all the major dimension for this product. Please refer to it for additional size information.
8. All units are available with or without grilles. Drawings show the standard grille lite division for the product as a stand-alone unit. When mulling with other units grille lite division may vary.
9. Unit may be mulled with others to form a combination unit. Rough Opening should be adjusted to account for the additional units. Generally, add the unit dimensions together and add 1/2" for the rough opening.
10. The standard jamb depth is 4-9/16". Jamb Extension may be added to increase the jamb depth up to 7-9/16". Specify exact jamb depth needed.
11. Exterior Dimensions with Brick Mold, add 2.75" to the width and add 2" to the height. Note: interior frame and rough opening dimensions are not affected.
12. Tempered glass is stocked for certain sizes. These sizes are marked with shaded glass. Stock Tempered glass is available for standard delivery schedule, all other tempered glass is special order.

Call Height - DH	Call Height - FX	Unit/Frame Height	R.O. Height	12	16	20	24	28	32	36	Call Width
				16"	20"	24"	28"	32"	36"	40"	Unit/Frame Width
			1'-4 1/2"	1'-4 1/2"	1'-8 1/2"	2'-0 1/2"	2'-4 1/2"	2'-8 1/2"	3'-0 1/2"	3'-4 1/2"	R.O. Width
12	16"	1'-4 1/2"	1'-4 1/2"	1 CDT1212	5 CDT1612	9 CDT2012	13 CDT2412	17 CDT2812	21 CDT3212	25 CDT3612	
16	20"	1'-8 1/2"	1'-8 1/2"	2 CDT1216	6 CDT1616	10 CDT2016	14 CDT2416	18 CDT2816	22 CDT3216	26 CDT3616	
20	24"	2'-0 1/2"	2'-0 1/2"	3 CDT1220	7 CDT1620	11 CDT2020	15 CDT2420	19 CDT2820	23 CDT3220	27 CDT3620	
24	28"	2'-4 1/2"	2'-4 1/2"	4 CDT1224	8 CDT1624	12 CDT2024	16 CDT2424	20 CDT2824	24 CDT3224	28 CDT3624	

Grille Patterns



No Grille



Colonial



Lexington

Call Height - DH	Call Height - FX	Unit/Frame Height	R.O. Height	40	44	52	60	68	Call Width
				44"	48"	56"	64"	72"	Unit/Frame Width
			3'-8 1/2"	3'-8 1/2"	4'-0 1/2"	4'-8 1/2"	5'-4 1/2"	6'-0 1/2"	R.O. Width
12	16"	1'-4 1/2"	1'-4 1/2"	29 CDT4012	33 CDT4412	37 CDT5212	41 CDT6012	45 CDT6812	
16	20"	1'-8 1/2"	1'-8 1/2"	30 CDT4016	34 CDT4416	38 CDT5216	42 CDT6016	46 CDT6816	
20	24"	2'-0 1/2"	2'-0 1/2"	31 CDT4020	35 CDT4420	39 CDT5220	43 CDT6020	47 CDT6820	
24	28"	2'-4 1/2"	2'-4 1/2"	32 CDT4024	36 CDT4424	40 CDT5224	44 CDT6024	48 CDT6824	